



Aplicación y propiedades

Características

Tubo muy flexible reforzado con una espiral rígida para resistir al impacto.

Temperatura de utilización

-20/+60°C

Utilización

Aspiración industrial, transporte de agua dulce y salada, soluciones químicas y sólidos abrasivos.

Presentación

Color gris con espiral en verde o con espiral azul.
Disponible en rollos de 50, 25 y 6 metros, dependiendo del diámetro.



Mangueras de PVC y poliuretano
PVC and polyurethane hoses

Application and properties

Features

Very flexible hose, reinforced with shock resistant pvc spiral.

Temperature range

-20/+60°C

Applications

Industrial suction and conveying fresh and salt water, chemical solutions and abrasive solids.

Presentation

Colour: grey and green / grey and blue
Available in lengths of 50, 25 and 5 meters, depending on the diameter.



Características técnicas / Technical features

	Diámetro interior Internal diameter		Peso Weight	R. curv. Bending R.	Presión Trabajo Working pressure	Vacío Vacuum	Long. del Rollo Coil Length
	mm	"	Kg	mm	bar	Mbar	m
H141019	19	3/4"	0,335	95	8	900	50
H141025	25	1"	0,4	125	8	900	50
H141032	32	1 1/4"	0,58	160	7	900	50
H141038	38	1 1/2"	0,68	190	7	900	50
H141050	51	2"	0,97	250	6	900	50
H141063	63	2 1/2"	1,405	315	5,5	900	50
H141075	76	3"	1,68	375	4	900	50
H141090	90	3 1/2"	2,055	425	4	900	25
H141100	102	4"	2,6	500	4	900	25
H141125	127	5"	4	625	4	900	25
H141150	152	6"	5,2	850	4	900	25
H141200	203	8"	8,5	1000	4	900	6

Otros diámetros, longitudes y características, a consultar. Fabricamos todo tipo de mangueras especiales.
Other dimensions, lengths or features available upon request. We manufacture any type of special hoses.